

Stryker 4.0 mm 30° Arthroscope, C-Mount, Speed-Lock™, 140 mm

SKU: MP49289



Categories: [Arthroscopes](#)

Description

Specifications:

Type of Scope: Arthroscope Part Number 502-527-030 Manufacturer Stryker Diameter 4.0 mm Angle 30° Working Length 140 mm Sterilization Autoclavable STERRAD Steris ETO Cidex Camera Connection C-Mount Locking Mechanism Speed-Lock Light Post Direction Standard Procedure Large Joint Arthroscopy - Knee, Shoulder Field of View 105° Compatible Hardware 5.0 mm Series Speed-Lock Hardware 377-031-144 5.0 mm Cannula, 2 Rotating Stopcocks 377-031-129 Pencil Tip Obturator for 5.0 mm Cannula 377-031-229 Trocar for 5.0 mm Cannula 5.8 mm Series Speed-Lock Hardware 747-031-560 5.8 mm Cannula, 2 Fixed Stopcocks 747-031-550 5.8 mm Cannula, 2 rotating Stopcocks 747-031-540 5.8 mm Cannula, 1 Fixed Stopcock 747-031-530 5.8 mm Cannula, 1 Rotating Stopcock 747-031-510 Pencil Tip Obturator for 5.8 mm Cannula 747-031-511 Blunt Tip Obturator for 5.8 mm Cannula 747-031-520 Trocar for 5.8 mm Cannula 6.5 mm Series Speed-Lock Hardware 377-031-650 6.5 mm Cannula, 2 Rotating Stopcocks 377-031-630 6.5 mm Cannula, 1 Rotating Stopcock 377-031-660 6.5 mm Cannula, 2 Fixed Stopcocks 377-031-640 6.5 mm Cannula, 1 Fixed Stopcock 377-031-610 Pencil Tip Obturator for 6.5 mm Cannula 377-031-611 Blunt Tip Obturator for 6.5 mm Cannula 377-031-620 Trocar for 6.5 mm Cannula 6.5 mm Inflow/Outflow Cannula 747-031-650 Inflow/Outflow Cannula, 2 Rotating Stopcocks (Continuous Flow) 747-031-510 Pencil Tip Obturator for 6.5 mm Inflow/Outflow Cannula 747-031-511 Blunt Tip Obturator for 6.5 mm Inflow/Outflow Cannula 747-031-520 Trocar for Inflow/Outflow Cannula